



PBC-2-12

DUAL CALL CORD w/PHONE PLUG



UL 1069 and CSA C22.2#205
5002971



BENEFITS

- High Impact Thermoplastic
- Durable 7 Foot Cord
- Easy to Install
- Easy to Operate
- Right Angel Phone Plug

The Tech Works **PBC-2-12** is a Push Button Call Cord made of high impact thermoplastic with 2-buttons, each on a 12 foot cord with a common right angle 1/4 inch phone plug. Designed to provide remote push button operation from the **NC-PBS-1** Emergency Push Button Station or the **PBS** generic patient bed station by simply plugging it into the jack. The button is a non-locking normally open contact passive assembly designed for use with Substations listed above. The cord set comes with a security clip and is completely shock and waterproof for use in sterile environments.

This device has been tested and is proven safe in oxygen rich environments.

Associated Equipment

NC-PBS-1	NC-Series Patient Bed Station
CC2-PBS	Patient Bed Station

Design Information

Power	N/A
Color	White
Mounting	1/4" Phone Jack
Dimensions	Housing - 2.375" L x 1.0" W
	Cords - 0.25" Dia. x 12' L x 18 AWG
	Plug - 0.25" Dia. 1.8" L x 1.6" H

Architects' and Engineers' Specifications

The Light Signaling System Call Cord shall be two standard normally open contact device constructed of thermoplastic and shall include a 1/4 inch phone plug for quick connect to wall mounted Stations. The Push Buttons shall be momentary non-locking assembly in a 2.375" long by 1.0" wide housing. The cord assembly shall be 0.25" in diameter with a plastic jacket and measure at least 12 feet in length. The device shall include a molded right angle 1/4 inch phone plug for connection to the signaling system and a security clip for attachment to patient furniture.

The Light Signaling System Room Status Call Cord shall be Tech Works Model PBC-2-12.



Tech Works®

"Making Specialized Communication Easy"