



The Tech Works VPKS-2 is a Vandal Resistant Key Switch station normally used as a remote reset or "Cancel" station on our VC-Series Intercom products and is specifically designed for the Security industry. With its pre-wired connections, it is easy to install and requires no maintenance. Designed for those locations where call cancel without enter a prison cell is required.

The Face Plate is made of 12-gauge Stainless Steel with a brushed finished and includes tamper resistant mounting screws. A 2 gang electrical box version is available upon request model VPKS-2.

The key switches are a moisture resistant design using 4 tumbler mortise cylinder type key switch. Both Normally Open and Normally Closed switch contacts are available for remote control of a variety of systems and applications. Matching keys are available upon request.

On the VPKS-2-2G the top switch is a momentary contact for resetting some remote stations while the bottom is a maintained contact for activating and deactivating remote stations. The top key can only be removed in the straight up and down position while the bottom key can be removed in either the "Enabled" or "Cancel" positions.

VPKS-2-2G

Vandal Proof Key Switch with 2 Key Switches on a 2 Gang Stainless Steel Plate

BENEFITS

- Rugged Design
- Easy to Install
- No Maintenance
- Designed Specifically for Corrections

Design Information:

Power	12 or 24 V DC
Color	Brushed 12-Gauge Stainless
Mounting	2 Gang
Dimensions	4.5" W x 4.5" H
Weight	~ 1 lb.

Architects' & Engineers' Specifications

The Correctional Grade Nurse Call Communication System Remote Call Cancel Reset Key Switch shall be a two gang electrical box-mounting device of moisture resistant design using 2, 4 tumbler mortise cylinder type key switches on a 12 gauge stainless steel faceplate with special mounting hardware to protect it from tampering and vandalism. One Key switch shall be a spring return monetary type and the other shall be a maintained contact allowing the key to be removed in either position. All Remote Call Cancel Reset Key Switches shall be keyed alike and delivered with 1 spare key for every switch. The remote reset station shall provide all latching and control circuitry for a single patient station and any associated corridor light and shall be a passive electronic device requiring no more than 30 mA at 24 Volts DC for full operation. The Remote Call Cancel Reset Key Switch shall be Tech Works Model VPKS-2-2G



Tech Works®

"Making Specialized Communication Easy"