



The Tech Works VPKS-2PRK-1 is a Vandal Resistant Key Switch station normally used as a remote Reset and Activation station on our CC-Series or VC-Series products and is specifically designed for the Security industry where the station may be subject to abuse or vandalism. With its pre-wired connections, it is easy to install and requires no maintenance. It is perfect for those locations where call cancel or station activation is required without enter a prison cell or patient room.

The Face Plate is made of 12-gauge Stainless Steel with a brushed finished and includes tamper resistant mounting screws. A 2 gang electrical box version is available upon request model VPKS-2.

The key switch is a moisture resistant design using 4 tumbler mortise cylinder type key switch. The contact is a maintained closure for activating and deactivating remote stations. The key can be removed in either the "ON" or "OFF" (Cancel) positions. Matching keys are available upon request.

VPKS-2PRK-1

Vandal Proof Key Switch 2 Position Removeable Key

BENEFITS

- Rugged Design
- Easy to Install
- No Maintenance
- Designed Specifically for Corrections

Design Information:

Power	12 or 24 V DC
Color	Brushed 12-Gauge Stainless
Mounting	1 Gang Back Box (2 Gang Optional)
Dimensions	2.75" W x 4.5" H
Weight	< 1 lb.

Architects' & Engineers' Specifications

The Correctional Grade Nurse Call Communication System Remote Call Cancel Reset Key Switch shall be a one or two gang electrical box-mounting device of moisture resistant design using 4 tumbler mortise cylinder type key switch on a 12 gauge stainless steel faceplate with special mounting hardware to protect it from tampering and vandalism. The key shall be removeable in either the "ON" or "OFF" positions. All Remote Call Cancel Reset Key Switches shall be keyed alike and delivered with 1 spare key for every switch. The remote reset station shall provide all latching and control circuitry for a single patient station and any associated corridor light and shall be a passive electronic device requiring no more than 30 mA at 24 Volts DC for full operation.

The Remote Call Cancel Reset Key Switch shall be Tech Works Model VPKS-2PRK-1



Tech Works®

"Making Specialized Communication Easy"